

Examination Lights

EXCEPTIONALLY BRIGHT LIGHT FOR EVERYDAY USE

HEINE Examination Lights incorporate the latest in illumination technology: Flexible halogen examination lights with innovative bulb technology for exceptional brightness.

The three different mounting options by wheeled stand, wall- or clamp-mounting provide ideal solutions for the daily practice environment.





HEINE® HL 5000 Examination Light

Powerful Universal Halogen Light



- ∴ Two flexible sections
- ∴ Exceptionally-high light output
- ∴ 140,000 Lux at 30 cm

With an exceptionally-high light output of 140,000 lux at a distance of 30 cm the HL 5000 Examination Light is ideal for examining and recognizing small details. The flexible gooseneck construction provides a working radius of 120 cm. Three versions are available: wheeled stand, wall mounting, multi-purpose clamp.

- ∴ **Long-lasting 12V/50W halogen bulb** gives 140,000 Lux light output at 30 cm. Very bright, white light.
- ∴ **Extremely compact illumination head.** No obstruction of view, ease of handling.
- ∴ **3 different mounting options: wall, table or wheeled stand.** Versatile.
- ∴ **Halogen bulb lasts at least 4000 hours.** Economical.
- ∴ **Additional UV filter.** Increased safety during examination.
- ∴ **Solid construction with high-specification 120 cm radius gooseneck design.** Super-wide radius of operation, easy to position, light stays put in any selected position.
- ∴ **Additional IR-Filter reduces heat.** More comfort for the patient and examiner.

HL 5000 Examination Light	12V/50W
on non-tip wheeled stand, metal base [01]	J-005.27.106
on lightweight wheeled stand L, polycarbonat base [02]	J-005.27.108
with wall mount [03]	J-005.27.102
with clamp mount [04]	J-005.27.104
Halogen spare bulb 12V/50W [05]	J-005.27.111



230V is the standard mains voltage. If a different voltage is required, e. g. 120V, please specify when ordering.

HEINE® HL 1200 Examination Light



- ∴ Two flexible sections
- ∴ Ultra-slim head
- ∴ 90,000 Lux at 30cm

- ∴ **Ultra-slim head.** More freedom of movement and an unobstructed view for the examiner.
- ∴ **Built-in temperature filter.** Avoids patient discomfort.
- ∴ **Exceeds all relevant quality standards.** Guaranteed protection for the patient even if e.g. a bulb fails.
- ∴ **“Stay-put” construction of flexible section.** Adjust the light to virtually any position and it “stays-put”, will not sag or droop.
- ∴ **Special non-tip wheeled stand.** Resists tipping to improve safety in clinic and practice.
- ∴ **Long-life 12V/20W lamp.** 4000 hours bulb life.
- ∴ **90,000 Lux light output at 30 cm.** Bright, white light.

HL 1200 Examination Light, 12V/20W	black	white
with wheeled stand, metal base [01]	J-005.27.068	J-005.27.067
with lightweight wheeled stand, polycarbonate base [02]	J-005.27.078	J-005.27.077
with additional multi-purpose clamp [03]	J-005.27.056	J-005.27.058
with wall-mounting bracket, can also be fitted to opt. wheeled stand [04]	J-005.27.052	J-005.27.054
Halogen spare bulb 12V/20W [05]	J-005.27.075	J-005.27.075



Wheeled stand (metal base) with mount for HL 1200 Light	Y-096.50.004
Wheeled stand (polycarbonate base) with mount for HL 1200 Light	Y-096.50.009
Mount for HL 1200 Light for wheeled stand	J-000.27.069
Black clamp, only	J-000.27.010
White clamp, only	J-000.27.012





HEINE® HKL Universal Fiber Optic (F.O.) Examination Light

The ideal light for any doctor's practice. Provides light similar to daylight. Can be powered by any HEINE F.O. Projector.


- ∴ **Adjustable Diaphragm Aperture.** Wide range of spot sizes. Bright, even light. No temperature increase.
- ∴ **Colour temperature 3800K.** "Daylight" illumination.
- ∴ **Long, flexible arm "stays put" where required.** Very flexible to position with long-reach arm.
- ∴ **Slimline head.** Unobstructed view.
- ∴ **Universal-mounting.** Suits the practitioner's needs.
- ∴ **Can be retro-mounted to existing projectors.** Makes an examination light out of any projector.
- ∴ **30,000 Lux light output at 20 cm with projector HK7000.**
- ∴ **Mounting options:**
 - on wheeled stand [01]
 - with clamp for table-top mounting (maximum 40mm thick) [02]
 - with clamp for vertical mounting to a tube up to 40mm dia. [03]
 - with clamp for mounting to square tube up to 40mm dia. [04]
 - wall-mounting for HK7000 Projector [05]



HKL Light	F.O.
on wheeled stand [01]	J-003.27.004
with clamp [02] [03] [04]	J-003.27.001
with wall-bracket [05]	J-003.27.002
Black clamp, only	J-000.27.010
White clamp, only	J-000.27.012
Base plate, only	J-000.27.011
Wheeled stand without base-plate	Y-096.50.001
Wheeled stand with base-plate	Y-096.50.002

Please order the projector separately. See page 170.

Light spot sizes



230V is the standard mains voltage. If a different voltage is required, e. g. 120V, please specify when ordering.